

# Cola<sup>®</sup>Lube 4715

## DEA-free, Long Chain Lubricant Additive

#### CHEMICAL NAME LISTINGS

Liquid, Long Chain Alkanolamide

US (TSCA); EU (REACH); Canada (DSL); Australia (AICS); Japan (ENCS); Philippines (PICCS); Korea (ECL); New Zealand (NZIoC); China (IECSC)

With the need for DEA-free metalworking additives, Colonial Chemical has developed an innovative product for use in soluble oils, semisynthetic and synthetic metal working fluids. **Cola®Lube 4715** is useful to the formulator in applications such as tapping, broaching, stamping, drilling and grinding. Cola®Lube 4715 will provide corrosion protection, antiwear and EP properties.

Cola<sup>®</sup>Lube 4715 is a low foaming, long chain alkanolamide that is dispersible in water. The product, when dispersed in the presence of water and oil, forms a chemical emulsion. Lubricants with specifically controlled viscosities can be developed due to the unique thickening properties of Cola<sup>®</sup>Lube 4715 in water. Cola<sup>®</sup>Lube 4715 is non-staining to ferrous and non-ferrous metal while providing ferrous corrosion protection to formulations.

#### **SPECIFICATIONS**

Appearance @ 25°C	White to tan solid
Color, Gardner '98 @ 50°C	10 Max.
pH (10% aq)	9.8 – 10.8
Acid value	10 Max.

#### SOLUBILITY IN OILS

10% solutions in the following oils:

	5
Aromatic 150	Soluble
Soy methyl ester	Soluble
100 cs. Paraffinic	Dispersible
Naphthenic	Dispersible
Isoparaffinic	Insoluble
Mineral seal oil	Insoluble

### PERFORMANCE TESTING RESULTS

Shake Foam Test (1 a Test Material into 50 ml DI water)

(Ty rest material line so file Di water)		
Immediate	65 mm	
1 min.	55 mm	
3 min.	55 mm	
5 min.	55 mm	
10 min.	54 mm	



#### STORAGE AND HANDLING

Cola<sup>®</sup>Lube 4715 should be stored in closed containers. Shelf life is 24 months from date of manufacture. Cola<sup>®</sup>Lube 4715 is shipped in steel 55-gal drums, net weight 450 lbs (204.1 kg). Safety Data Sheet may be downloaded at www.colonialchem.com.

# **Colonial** Chemical

225 Colonial Drive • South Pittsburg, TN 37380 Phone: 423-837-8800 • Fax: 423-837-3888 www.colonialchem.com

Innovative Specialty Surfactants

Technical information contained herein is believed to be accurate. However, it is furnished without charge or obligation and is given and accepted at the recipient's sole risk. No guarantee of the accuracy of the information is made and the products discussed are sold without conditions or warranties expressed or implied. No warranties beyond the guarantee that Colonial Chemical products are manufactured to specs are expressed or implied, since the use of material is beyond our control. Purchasers should make their own tests and determine suitability of the product for their particular purposes. Nothing contained herein shall be considered a recommendation for any use that may infringe upon patent rights. Safety information regarding this product is contained in its Safety Data Sheet. © 2022, Colonial Chemical, Inc. All rights reserved. 3/22